









FOR THRONE





PACKAGE CONTENTS

2x Armrests (pre-installed)

ACCESSORIES BOX CONTENTS

2x Lever Handles (For multi-tilt only)

1x Chair Backrest

1x Wheelbase

Σ

ш

S

1x Chair Seatbase

1x Tilt Mechanism

1x Accessories Box

5x Casters (Wheels) **1x** Hydraulic Piston

2x Side Covers

4x M8 Screws

1x Allen Key

8x Spring Washers

2x Phillips (Cross) Screws

YOU WILL ALSO NEED

the Allen key.

1x Phillips (Cross) Head Screwdriver

Push the bracket on the left side inwards

to meet the backrest, and secure using the

M8 screws. Tighten all 4 screws fully using

Attach the full-tilt mechanism to the

screws. Ensure the mechanism is in

the correct direction. Skip to step 11.

bottom of the seatbase using the 4 M8

BACKREST RECLINE

Pull the lever FULLY and lean back slowly until desired angle is achieved, then slowly return the lever to its starting position. Ensure the lever locks back in place.



MULTI-TILT MECHANISM

Right lever (while seated): Pull up to adjust height. Left lever (while seated): Push down/pull up to lock/unlock the tilt mechanism.



4D ARMRESTS armrest to adjust height.



FULL-TILT MECHANISM mechanism.

CAUTION: Do not adjust the recline lever until the backrest has been securely installed (Step 6). Doing so may cause the backrest bracket to spring forward.





Turn the wheelbase the right side up and insert the hydraulics piston. Slide the hydraulics sleeve over the piston.











firmly.

Line up the grooves inside the lever handles with the notches and insert



FOR OMEGA / TITAN

Remove all parts from the box, while taking care to avoid the backrest recline lever and backrest bracket. Check if there are any missing parts.















Press and hold the 1) front button to adjust front, back, and angle, 2) inner side button to adjust sideways, and 3) lever on the outside of the

Right lever (while seated): Pull up to adjust height. Push inwards/pull outwards to lock/unlock the tilt

TILT TENSION

Turn the knob clockwise to loosen the rocking tension of the chair, anti-clockwise to tighten. Adjust according to your weight.



ARMREST ADJUSTMENT

The distance between armrests can be adjusted. Loosen the M8 screws at the bottom of the armrests and move to the desired position, then tighten to secure.

LUMBAR ADJUSTMENT Turn the knob clockwise to increase the lumbar support, anticlockwise to decrease. Do not attempt to turn past the maximum and minimum.



The recommended weight load for 100kg (220lbs) for the Throne series, 110kg (240lbs) for the OMEGA series, and 130kg (290lbs) for the TITAN series. The chair should only be used normally and in a non-abusive manner. For warranty information, please visit the Warranty section on our website.

Lay out the foam sheets found in the packaging on a flat surface. Place the wheelbase upside down on top of the foam and insert the 5 casters.



Align the backrest with the bracket on the right side of the chair. Attach the backrest using the M8 screws.



Attach the multi-tilt mechanism to the bottom of the seatbase using the 4 M8 screws. Ensure the mechanism is in the correct direction. Proceed to Step 10.



FOR OMEGA / TITAN

Carefully tilt the chair upwards while holding the wheelbase and position it upright. Congratulations! You've assembled your Secretlab chair.



